



HIGHLIGHTS

- **AC/DC voltage/current up to 1050V/30A**
- **Basic uncertainty 9 ppm**
- **AC/DC power, energy, resistance, capacitance, frequency, TC, RTD**
- **Scope options up to 1100 MHz**
- **High voltage resistance option for 1.5 kV insulation testers**
- **Built-in process multimeter**
- **RS232, LAN, USB and GPIB interfaces as standard**

DESCRIPTION

Multifunction calibrator 9020 is designed as universal calibration tool for electrical calibration laboratories, covering most of their workload like multimeters, 6½ digit DMMs, clamp meters, ohm meters, power meters and power analyzers, energy meters, transducers, insulation testers, process meters, scopes and many others. High load capacity of both voltage (up to 50 mA) and current output allows for calibration of high-consumption analogue meters. Installed harmonic and non-harmonic shape signals allow for testing meter sensitivity to distorted signals by a signal with various crest factor.

Compared to its predecessor, 9020 brings wider frequency ranges in both AC voltage and AC current functions, improved accuracy in most functions, 2MHz frequency output with duty cycle and advanced impedance source to match the latest 6½ digit DMM workload.

9020 calibrator can be fully integrated into commonly used calibration automation platforms. Unique camera readout module CamOCR, available in Meatest's SW package Caliber/WinQbase, allows for semi-automated calibrations of multimeters with no remote control interface.

Option	Description
SCO / SC1	Scope extension for calibration of oscilloscopes up to 400 MHz (1.1 GHz with SC1). Comes with N/BNC adapter.
HVR	High voltage resistance extension for calibration of insulation testers and megaohmmeters up to 1.5 kV. Comes with 191-11 5kV cable.
MER	Multimeter extension for calibration of transducers and imitation of strain gauges and other industrial sensors. Comes with 9000-60 cable.

SPECIFICATION

All absolute uncertainty specifications in this document are defined at a confidence interval of 95%, extension coefficient $k = 2$. Product specifications include 12-month stability, resolution (in measurement functions if any), temperature and humidity effects (within specified limits), linearity, load and line regulation and uncertainty of calibration standards (calibration traceability).

GENERAL DATA

Warm-up time	30 minutes
Reference temperature	+21 °C – +25 °C
Operating temperature	+13 °C – +33 °C
Storage temperature	-10 °C – +55 °C
Temperature coefficient	10 % of accuracy / °C outside T_{REF}
Max relative humidity	70 %
Power supply	115/230V - 50/60 Hz, 450 VA max
EMC compliance	Safety class I according to IEC 61010 ed. 2 ESD class I according to EN 61326 Overvoltage CAT II
Dimensions (W x H x D)	434 x 191 x 641 mm
Weight	24 - 25 Kg depending on options installed
Interfaces	RS232, IEEE488, USB, Ethernet

DC/AC Voltage

Voltage range summary	DC: 0 mV – 1050 V AC sine: 1 mV _{RMS} – 1050 V _{RMS} Non-sine: 1 mV _{RMS} – 200 V _{RMS}
Internal ranges	20 mV, 200 mV, 2 V, 20 V, 100V, 280 V, 1050 V
Frequency accuracy and resolution	5 ppm, 5 digit
Non-sine waveform types	saw, triangle, square, truncated sin; 1kHz max; uncertainty: 0.21 % + 0.1 % of range + 70 μ V _{PK}
Voltage output modes	passive 50 Ω output up to 200 mV _{DC} active output in all DC and AC ranges

Ranges, resolution, 1 year uncertainty [ppm of value]

Range	DC	3 Hz – 10 Hz	10 Hz – 20 kHz	20 kHz – 50 kHz	50 kHz – 100 kHz	100 – 300 kHz
1.00000 – 20.00000 mV	30 + 1.5 μ V ^{*1}	2 500 + 25 μ V	1 400 + 15 μ V	1 500 + 30 μ V	2 500 + 35 μ V	4 500 + 100 μ V
20.0000 – 200.0000 mV	15 + 1.5 μ V ^{*1}	2 150 + 20 μ V	250 + 10 μ V	350 + 15 μ V	1 000 + 50 μ V	4 500 + 100 μ V
0.200000 – 2.000000 V	11 + 4 μ V	2 150 + 100 μ V	165 + 90 μ V	300 + 100 μ V	700 + 200 μ V	2 000 + 800 μ V
2.00000 – 20.00000 V ^{*2}	8 + 25 μ V	2 150 + 1 mV	160 + 700 μ V	300 + 1.2 mV	600 + 2 mV	2 000 + 5 mV
20.0001 – 100.0000 V	13 + 150 μ V	2 150 + 6 mV	180 + 5 mV	300 + 14 mV	1 000 + 14 mV	N/A
100.0001 – 280.0000 V ^{*3}	15 + 300 μ V	2 150 + 13 mV	180 + 10 mV	300 + 40 mV	N/A	N/A
280.000 – 1050.000 V ^{*4}	20 + 3.5 mV	N/A	250 + 30 mV	N/A	N/A	N/A

*1 Uncertainty in passive mode. Active mode uncertainty is 100 ppm + 10 μ V and 15 ppm + 10 μ V respectively.

*2 Frequency is limited to 100 kHz above 12 V.

*3 Frequency is limited to 3 Hz – 10 kHz above 210 V.

*4 Frequency is limited to 20 Hz – 10 kHz.

Distortion and Load Characteristics

Parameter	Range	20mV	200mV	2V	20V	100 V	280V	1050V
THD + noise ^{*5}	3 – 10 Hz	0.25 % + 200 μ V	0.25 % + 300 μ V	0.25 %	0.25 %	0.25 %	0.25 %	N/A
	10 – 45 Hz	0.05 % + 200 μ V	0.05 % + 300 μ V	0.15 %	0.15 %	0.15 %	0.15 %	0.25 %
	45 – 20000 Hz	0.05 % + 200 μ V	0.05 % + 300 μ V	0.05 %	0.05 %	0.05 %	0.05 %	0.20 %
	20 – 50 kHz	0.25 % + 200 μ V	0.25 % + 300 μ V	0.12 %	0.15 %	0.3 %	0.7 %	N/A
	50 – 100 kHz	0.35 % + 230 μ V	0.35 % + 300 μ V	0.22 %	0.3 %	0.5 %	N/A	N/A
	100 – 300 kHz	1.5 % + 500 μ V	1 % + 700 μ V	0.7 %	2.5 %	N/A	N/A	N/A
Burden current	DC active	1 mA	5 mA	30 mA	50 mA	50 mA	50 mA	5 mA
	3 – 20000 Hz	0.5 mA _{RMS}	4 mA _{RMS}	30 mA _{RMS}	50 mA _{RMS}	50 mA _{RMS}	40 mA _{RMS}	4 mA _{RMS}
	20 – 50 kHz	0.5 mA _{RMS}	4 mA _{RMS}	10 mA _{RMS}	10 mA _{RMS}	10 mA _{RMS}	10 mA _{RMS}	N/A
	50 – 100 kHz	0.5 mA _{RMS}	2 mA _{RMS}	5 mA _{RMS}	5 mA _{RMS}	N/A	N/A	N/A
	100 – 300 kHz	100 Ω min. load	100 Ω min. load	1 mA _{RMS}	5 mA _{RMS}	N/A	N/A	N/A

*5 THD in bandwidth up to 500 kHz or 10 lowest harmonics.

DC/AC Current

Current range summary	DC: 0.0000 μ A – 30.00000 A AC Sine: 10.0000 μ A _{RMS} – 30.00000 A _{RMS} Non-sine: 100.0000 μ A _{RMS} – 2.000000 A _{RMS}
Internal ranges	200 μ A, 2 mA, 20 mA, 200 mA, 2 A, 20.5 A, 30 A
Frequency accuracy and resolution	5 ppm, 5 digit
Non-sine waveform types	saw, triangle, square, truncated sin; 1kHz max.
Non-sine amplitude uncertainty	0.21 % of value + 0.1 % of range + 0.7 μ A _{pk}

Ranges, resolution, 1 year uncertainty [ppm of value]

Range	DC	10 Hz – 1 kHz	1 kHz – 5 kHz	5 kHz – 10 kHz	10 kHz – 30 kHz
10.0000 – 200.0000 μ A	200 + 12 nA	400 + 20 nA ^{*6}	450 + 25 nA ^{*6}	3 000 + 100 nA ^{*6}	5 500 + 900 nA ^{*6}
0.200000 – 2.000000 mA	150 + 30 nA	400 + 150 nA	450 + 200 nA	2 500 + 600 nA	4 000 + 5 μ A
2.000000 – 20.000000 mA	100 + 600 nA	300 + 1 μ A	400 + 2 μ A	2 000 + 6 μ A	4 000 + 10 μ A
20.00000 – 200.00000 mA	100 + 2 μ A	300 + 20 μ A	400 + 25 μ A	2 000 + 60 μ A	4 000 + 100 μ A
0.200000 – 2.000000 A ^{*7}	160 + 50 μ A	300 + 100 μ A	450 + 250 μ A	2 500 + 500 μ A	12 000+ 800 μ A
2.00000 – 20.50000 A	250 + 500 μ A	650 + 3 mA	N/A	N/A	N/A
20.50000 – 30.00000 A ^{*8}	450 + 750 μ A	1 200 + 5 mA	N/A	N/A	N/A

*6 Accuracy not specified below 10 μ A.

*7 Frequency is limited to 10 kHz above 500 mA.

*8 Continuous operation in case of good air flow and in reference temperature range. Built-in overheat sensor.

Distortion and Load Characteristics

Parameter	Range	200 μ A	2mA	20mA	200mA	2A	30A
Max. inductive load	10 Hz – 30 kHz	1 H	100 mH	100 mH	10 mH	1 mH	500 μ H
	10 Hz – 1 kHz	0.2 %	0.2 %	0.2 %	0.2 %	0.2 %	0.3 %
THD + noise ^{*9}	1 kHz – 5 kHz	0.2 %	0.2 %	0.2 %	0.2 %	0.2 %	N/A
	5 kHz – 10 kHz	0.5 %	0.4 %	0.4 %	0.4 %	1.5 %	N/A
	10 kHz – 30 kHz	0.8 %	0.8 %	0.8 %	0.8 %	N/A	N/A
Compliance voltage	DC	5 V	5 V	10 V	10 V	5 V	5 V
	10 Hz – 1 kHz	4 V _{rms}	4 V _{rms}	5 V _{rms}	5 V _{rms}	3.5 V _{rms}	3 V _{rms}
	1 kHz – 5 kHz	4 V _{rms}	4 V _{rms}	5 V _{rms}	5 V _{rms}	3.5 V _{rms}	N/A
	5 kHz – 10 kHz	2 V _{rms}	2 V _{rms}	2 V _{rms}	2 V _{rms}	1.5 V _{rms}	N/A
	10 kHz – 30 kHz	1 V _{rms}	1 V _{rms}	1 V _{rms}	1 V _{rms}	N/A	N/A
Load adder ^{*10}	DC	50 nA/V	50 nA/V	200 nA/V	2 μ A/V	100 μ A/V	500 μ A/V
	10 Hz – 1 kHz	70 nA/V	100 nA/V	200 nA/V	2 μ A/V	100 μ A/V	500 μ A/V
	1 kHz – 5 kHz	1.5 μ A/V	1.5 μ A/V	1.5 μ A/V	2 μ A/V	200 μ A/V	N/A
	5 kHz – 10 kHz	2 μ A/V	2 μ A/V	2 μ A/V	3 μ A/V	3 000 μ A/V	N/A
	10 kHz – 30 kHz	4 μ A/V	5 μ A/V	10 μ A/V	10 μ A/V	N/A	N/A

*9 THD in bandwidth up to 100 kHz

*10 Additional uncertainty for compliance voltage above 0.5 VRMS

Voltage from current

Voltage range	2.5000 mV – 5.00000 V
Waveform	DC, 10.000 Hz – 400.00 Hz sine
Amplitude uncertainty	0.05 % + [0.02 – 0.04] % of range
Distortion	< 0.1 % in 100 kHz bandwidth
Source impedance	2.2, 22 or 220 Ω

Current coil (option 0950)

Applicable multiplier	2 – 200
Max. simulated current	multiplier \times 30 A (1500 A with 0950 Current Coil)
Frequency range	45 – 65 Hz
Additional uncertainty	0.3 % with 0950 Current Coil

Resistance & Capacitance

Range summary

0.0000 Ω – 100.0000 kΩ in 4W
0.0000 Ω – 1.100000 GΩ in 2W & 2W COMP
0.600000 nF – 120.0000 mF in 2W

Resolution:

6½ digits, 0.1 mΩ max

Variable Resistance & Capacitance source, 1 year uncertainty

Resistance range ^{*11}	Uncertainty ^{*12}
0 – 10 Ω	35 ppm + 2 mΩ
10 – 33 Ω	30 ppm + 2 mΩ
33 – 1000 Ω	30 ppm + 3 mΩ
1 – 10 kΩ	30 ppm + 30 mΩ
10 – 100 kΩ	30 ppm + 300 mΩ
100 – 330 kΩ	30 ppm + 3 Ω
330 – 1000 kΩ	50 ppm + 3 Ω
1 – 3.3 MΩ	50 ppm + 30 Ω
3.3 – 10 MΩ	100 ppm + 30 Ω
10 – 100 MΩ	0.2 % + 300 Ω
100 – 330 MΩ	0.3 % + 3 kΩ
330 – 1100 MΩ	1 % + 10 kΩ

Capacitance range ^{*11}	Uncertainty
0.6 – 3.3 nF	0.15 % + 10 pF
3.3 nF – 100 μF	0.15 %
0.1 – 20 mF	0.25 %
20 – 120 mF	0.45 %

*11 Variable source range boundaries are based on calibration values of fixed standards and as such may differ from nominal range boundaries by up to 10 %. 2mF, 20mF and 120mF ranges are always nominal.

*12 Uncertainty in 4W and 2W COMP modes. Add 30 mΩ in 2W mode. Uncertainty is specified for test voltages above 0.1 V

Fixed Resistance & Capacitance standards, 1 year uncertainty

Fixed resistor nominal value	Uncertainty ^{*13}
0 Ω, 0.1 Ω, 1 Ω	0.5 mΩ
10 Ω	1 mΩ
33 Ω	2 mΩ
100 Ω	3 mΩ
330 Ω	25 ppm
1 kΩ, 3.3 kΩ, 10 kΩ, 33 kΩ, 100 kΩ	15 ppm
330 kΩ, 1 MΩ	20 ppm
3.3 MΩ	80 ppm
10 MΩ	130 ppm
33 MΩ	250 ppm
100 MΩ	1000 ppm
330 MΩ	1500 ppm
1 GΩ	2500 ppm

Fixed capacitor nominal value	Uncertainty ^{*14}
1 nF	0.30 %
3.3 nF	0.25 %
10 nF	0.12 %
33 nF	0.12 %
100 nF	0.12 %
330 nF	0.12 %
1 μF	0.12 %
3.3 μF	0.12 %
10 μF	0.12 %
33 μF	0.15 %
100 μF	0.15 %

*13 Uncertainty in 4W mode. Add 30 + (0.015 / test current) milliohms in 2W mode

*14 Specification applies to Relative mode of capacitance, for Absolute mode add additional floor 15 pF.

Temperature (RTD, TC)

RTD temperature standards

Pt385, Pt3916, Pt3926, Ni672, Cu427, Cu428, custom

RTD R₀ range

20 Ω – 2 kΩ

Thermocouple types

A, B, C, D, E, G, J, K, L, M, N, R, S, T, U, XK

TC cold junction compensation

Manual or automatic with adapter 91

Uncertainty

0.01 °C – 0.07 °C in RTD
0.05 °C – 0.55 °C in TC

Frequency

Frequency range

0.10000 Hz – 2.00000 MHz

Frequency accuracy

5 ppm

Waveform type

positive squarewave 100 mV_{pk}, 1 V_{pk}, 3 V_{pk}

Amplitude accuracy

20 %

Duty cycle

Duty cycle range

0.1 % – 99.9 %

Accuracy

0.05 %

Frequency range

0.1 Hz – 1 kHz

Voltage range

1 mV_{pk} – 28.2 V_{pk}

Amplitude accuracy

0.5 % + 100 μV

AC/DC Power & Energy

Range summary	power: 40 μ W – 31.5 kW voltage: 0.2 V – 1050 V current: 0.2 mA – 30 A frequency: DC, 15 – 1000 Hz time period: 2 s – 1 hour
Total uncertainty	based on voltage, current, phase shift and energy period specifications.
Phase shift uncertainty	0.15° up to 200 Hz 0.25° above 200 Hz 0.5° in 1050V range, 20 – 500 Hz
Energy period uncertainty	0.01% + 0.3 s
Additional features	Harmonic distortion, voltage from current, current coil multiplication

Total 1 year power accuracy in common applications [% of value]

Set current	EU grid power (230 V, 50 Hz)	US grid power (115 V, 60 Hz)	Aircraft onboard power (115 V, 400 Hz)	Ship onboard power (440 V, 60 Hz)
100 mA	0.071 %	0.071 %	0.071 %	0.074 %
1 A	0.069 %	0.069 %	0.069 %	0.073 %
10 A	0.111 %	0.111 %	0.111 %	0.114 %
30 A	0.142 %	0.142 %	0.142 %	0.144 %

Harmonic distortion (all AC functions)

Number of harmonic products	50
Fundamental harmonic uncertainty	amplitude: $\geq 0.2\%$ of range frequency: 25 ppm phase shift: 0.2 – 0.5°
Frequency range	1 st product: 15 – 1000 Hz 2 nd – 50 th product: 30 – 5000 Hz
Harmonic product amplitude range	0 – 30 % of fundamental
Harmonic product phase shift unc.	5 μ s (typical)

MER Multimeter option

Measurement function	Range	Uncertainty
DC voltage	12 mV 120 mV, 1.2 V, 12 V	50 ppm + 3 μ V 50 ppm + [5 – 500] μ V
DC current	100 μ A, 1 mA 2.4 mA, 24 mA	200 ppm + [20 – 100] nA 150 ppm + 800 nA
Frequency	0.1 Hz – 100 kHz	50 ppm
Resistance ^{*15}	2 k Ω , 20 k Ω	200 ppm + [10 – 50] m Ω
RTD temperature ^{*15}	Pt3850, Pt3851, Pt3916, Pt3926, Ni120, custom	0.08 – 0.42 °C
TC temperature	BCDEG ₂ JKMNRST	0.22 – 1 °C

*15 Using 9000-60 4W measurement adapter (comes as standard with MER option)

HVR High Voltage Resistance option

Resistance range	Maximum test voltage	Resistance uncertainty	Test voltage uncertainty
100 – 200 k Ω	800 V _{DC}	0.2 %	0.3 % + 2 V
200 k Ω - 1 M Ω	1100 V _{DC}	0.2 %	0.3 % + 2 V
1 – 10 M Ω	1150 V _{DC}	0.3 %	0.5 % + 5 V
10 M Ω – 1 G Ω	1500 V _{DC}	0.5 %	0.5 % + 5 V
1 – 10 G Ω	1500 V _{DC}	1.0 %	1 % + 5 V
100 G Ω (fixed standard)	1500 V _{DC}	3.0 %	1.5 % + 5 V

SCO Frequency / Scope option

HF mode (levelled sine)

Amplitude range 1.400 mV_{PK} – 1.5000 V_{PK}

Freq. range	15 Hz – 100 kHz	100 – 500 kHz	0.5 – 10 MHz	10 – 100 MHz	100 – 400 MHz
Harmonic distortion	-55 dB	-38 dB (< 10 dBm)	-38 dB (< 10 dBm)	-38 dB (< 10 dBm)	-30 dB (< 10 dBm)
Flatness	< 0.2 % + 100 μV _{PK}	< 0.7 % + 100 μV _{PK}	< 1.2 % + 100 μV _{PK}	< 2.0 % + 200 μV _{PK}	< 2.5 % + 200 μV _{PK}
Amplitude uncertainty	0.5 % + 350 μV _{PK}	2.0 % + 250 μV _{PK}	2.5 % + 250 μV _{PK}	3.3 % + 250 μV _{PK}	3.7 % + 250 μV _{PK}

LF mode (DC, square wave)

High voltage range 0 – 200 V_{PK} at 1 kHz max, 0.3 % amplitude uncertainty
 Low voltage range 0 – 10.5 V_{PK} at 100 kHz max, 0.1 – 0.2 % amp. uncertainty

PULSE WIDTH and TIME MARKER modes

Frequency range 0.1 Hz – 400 MHz
 Frequency uncertainty 2.5 ppm
 Amplitude ranges 50 mV_{PK}, 100 mV_{PK}, 500 mV_{PK}, 1 V_{PK}
 Duty cycle ratios 1 – 50 %
 TM waveforms PWM up to 25 MHz, 2 ns spike otherwise
 Jitter < 2 ns
 Rise time < 1 ns

TRIGGER mode

Amplitude > 1 V_{PK}
 Division ratio off, /1, /10, /100
 Frequency range 15 Hz – 400 MHz
 Rise time < 1 ns

Input impedance measurement

Ranges 100 Ω, 2 MΩ
 Measurement accuracy 0.1 % in 10 – 100 % of range

SC1 Frequency / Scope option

HF mode (levelled sine)

Amplitude range 1.400 mV_{PK} – 1.5000 V_{PK} up to 1 GHz
 1.400 mV_{PK} – 1.0000 V_{PK} above 1 GHz

Freq. range	15 Hz – 100 kHz	100 – 500 kHz	0.5 – 10 MHz	10 – 100 MHz	100 – 600 MHz	600 – 1100 MHz
Harmonic distortion	-55 dB	-33 dB (< 10 dBm)	-33 dB (< 10 dBm)	-33 dB (< 10 dBm)	-30 dB (< 10 dBm)	-30 dB (< 10 dBm)
Flatness	< 0.2 % + 100 μV _{PK}	< 0.7 % + 100 μV _{PK}	< 1.2 % + 100 μV _{PK}	< 2.0 % + 100 μV _{PK}	< 2.5 % + 200 μV _{PK}	< 4.5 % + 200 μV _{PK}
Amplitude uncertainty	0.5 % + 350 μV _{PK}	2.0 % + 250 μV _{PK}	2.5 % + 250 μV _{PK}	3.3 % + 250 μV _{PK}	3.7 % + 250 μV _{PK}	6.5 % + 300 μV _{PK}

PULSE WIDTH and TIME MARKER modes

Frequency range 0.1 Hz – 400 MHz square wave
 400 – 1100 MHz sine
 Frequency uncertainty 0.1 ppm
 Amplitude ranges 50 mV_{PK}, 100 mV_{PK}, 500 mV_{PK}, 1 V_{PK}
 Duty cycle ratios 1 – 50 %
 TM waveforms PWM up to 25 MHz, 2 ns spike otherwise
 Jitter < 2 ns
 Rise time < 1 ns

LF mode, TRIGGER mode and Input impedance measurement function specifications are the same as in SCO option.